

TECHNICAL SPECIFICATIONS		KASHIKOI 5100X+	
DESCRIPTION	UNIT		
Tonnage Class		1.0TR	1.5TR
Star Rating	No. of BEE Stars	5	5
Unit	Model Number	RSB512HBEAP	RMB518HBEAP
IDU	Model Number	ESB512HBEAP	EMB518HBEAP
ODU	Model Number	CSB512HBEAP	CMB518HBEAP
Compressor	Type	Rotary	Rotary
Rated Power Supply	Volts/Hz/Phase	230/50/1	230/50/1
Rated Cooling Capacity	BTU/Hr	12215	18000
Maximum Cooling Capacity		15015	19800
Rated Cooling Capacity	Watts	3580	5275
Maximum Cooling Capacity		4400	5800
Rated Power Input	Watts	741	1368
ISEER		6.10	5.20
Cooling Seasonal Energy Consumption	(kWh)	455	786
Current Drawn (Rated)	Amps	3.6	6.3
Fan Speed	Steps	3	3
Air Flow (IDU) (Cooling -Super High)	CFM	484	583
Sound Level* (IDU)	dB	28	33
Dimension (IDU) (W x H x D)	mm	997 x 294 x 253	997 x 294 x 253
Dimension (ODU) (W x H x D)	mm	750 x 548 x 288	750 x 548 x 288
Net Weight (IDU)	Kg	13	13
Net Weight (ODU)	Kg	33	38
Refrigerant Pipe Diameter (Liquid Pipe/Suction Pipe)	mm	6.35/9.53	6.35/12.70
Maximum Piping length	Mtr	25	25

Features may vary from model to model. *At Super Silent fan speed & at a distance of 1m . Hitachi air-conditioners are designed to work in ambient temperatures upto 52°C. Due to continous research & development, specifications & features may change without prior notice. 6.1 ISEER is available in 1.0TR Model.