

TECHNICAL SPECIFICATIONS		STAR SUMO	
DESCRIPTION	UNIT		
Tonnage Class		2.5TR	3.25TR
Star Rating	No. of BEE Stars	1	NA
Unit	Model Number	RBZ130HBDW	RBZ039HBDW
IDU	Model Number	EBZ130HBDW	EBZ039HBDW
ODU	Model Number	CBZ130HBDW	CBZ039HBDW
Compressor	Type	Rotary	TWIN ROTARY
Rated Power Supply	Volts/Hz/Phase	230/50/1	400/50/3
Rated Cooling Capacity	BTU/Hr	29770	39000
Rated Cooling Capacity	Watts	8725	11430
Rated Power Input	Watts	2800	4200
ISEER		3.12	2.72
Cooling Seasonal Energy Consumption	(kWh)	2168	3251
Current Drawn	Amps	12.5	7.5/PHASE
Fan Speed	Steps	3	3
Air Flow (IDU) (Cooling -Super High)	CFM	812	812
Sound Level* (IDU)	dB	43	43
Dimension (IDU) (W x H x D)	mm	1259 x 362 x 282	1259 x 362 x 282
Dimension (ODU) (W x H x D)	mm	935 x 735 x 390	935 x 735 x 390
Net Weight (IDU)	Kg	19.5	19.5
Net Weight (ODU)	Kg	75	85
Refrigerant Pipe Diameter (Liquid Pipe/Suction Pipe)	mm	9.52/19.05	9.52/19.05
Maximum Piping Length	Meter	25	25

Features may vary from model to model. *At Super Silent fan speed & at a distance of 1m . Hitachi air-conditioners are designed to work in ambient temperatures upto 52°C. Due to continous research & development, specifications & features may change without prior notice.