

TECHNICAL SPECIFICATIONS		KAZE PLUS ECO		
DESCRIPTION	UNIT			
Tonnage Class		1.0TR	1.5TR	1.5TR
Star Rating	No of BEE Stars	3	2	3
Unit	Model Number	RAW312KXDAI	RAW218KXDAI	RAW318KXDAI
Compressor	Type	ROTARY	ROTARY	ROTARY
Rated Power Supply	Volts/Hz/Phase	230/50/1	230/50/1	230/50/1
Rated Cooling Capacity	BTU/Hr	12300	18000	18000
Rated Cooling Capacity	Watts	3605	5275	5275
Rated Power Input	Watts	1167	1825	1707
ISEER		3.09	2.89	3.09
Current Drawn	Amps	5.2	8.1	7.5
Fan Speed	Steps	3	3	3
Air Flow (Super High)	CFM	300	475	475
Sound Level*	dB	50	50	50
Dimension (W x H x D)	mm	600 x 380 x 560	600 x 428 x 680	600 x 428 x 680
Net Weight	Kg	36.8	52	52
Refrigerant	Name	R-410A	R-410A	R-410A
Remocon	Type	Wireless	Wireless	Wireless

Features may vary from model to model. Some of the models may not be available at all Hitachi outlets. *At Super silent fan speed & at a distance of 1m, Hitachi air-conditioners are designed to work in ambient temperatures upto 52°C. Due to continuous research and development, specifications, features and model colour may change without any prior notice.