

DESCRIPTION	UNIT	KASHIKOI 5300FX		
Tonnage Class		1.2TR	1.5TR	2.0TR
Star Rating	No. of BEE Stars	5	5	5
Unit	Model Number	RSNG514ACEA	RSOG518ACEA	RMOG524ACEA
IDU	Model Number	ESNG514ACEA	ESOG518ACEA	EMOG524ACEA
ODU	Model Number	CSNG514ACEA	CSOG518ACEA	CMOG524ACEA
Compressor	Type	Rotary	Rotary	Twin Rotary
Rated Power Supply	Volts/Hz/Phase	230/50/1	230/50/1	230/50/1
Rated Cooling Capacity (100 % load)	BTU/Hr	14400	18000	24000
Maximum Cooling Capacity	BTU/Hr	15840	20600	26100
Rated Cooling Capacity (100 % load)	Watts	4220	5275	7034
Maximum Cooling Capacity	Watts	4640	6040	7650
Rated Power Input (100 % load)	Watts	1090	1420	2070
Rated ISEER		5.00	5.00	4.70
Cooling Seasonal Energy Consumption	(kWh)	653.26	816.15	1158.94
Current Drawn (Rated)	Amps	5.0	6.5	9.5
Fan Speed	Steps	5	5	5
Airflow (IDU) (Cooling -Super High)	CFM	515	583	620
Sound Level* (IDU)	dB	28	31	37
Dimension (IDU) (W X H X D)	mm	968 X 294 X 240	997 X 294 X 258	997 X 294 X 258
Dimension (ODU) (W X H X D)	mm	750 X 548 X 288	750 X 548 X 288	792 X 600 X 299
Net Weight (IDU)	Kg	11.20	13.00	13.00
Net Weight (ODU)	Kg	31.50	33.80	47.60
Suction Line Diameter	mm (Inches)	9.53 (3/8")	12.7 (1/2")	15.88 (5/8")
Liquid Line Diameter	mm (Inches)	6.35 (1/4")	6.35 (1/4")	6.35 (1/4")
Maximum Piping Length	Mtr	25	25	25

Features may vary from model to model.

*At Super silent fan speed & at a distance of 1 m.

Hitachi Air Conditioners are designed to work in ambient temperature up to 52°C.

Stabiliser-free operation in inverter series is in standard test condition & within specified voltage range.

Images of remote & Indoor Unit is just for representation purpose only, actual product appearance may vary model to model.

Due to continuous research & development, specifications, features and look may change without prior notice.