

SPECIFICATIONS SPLIT AC - INVERTER MODELS

| | DESCRIPTION | UNIT | KASHIKOI 5400X | | |
|--------------------------------------|---|--------------------|-------------------------|-------------------------|------------------------------|
| | | | 5 | 5 | 5 |
| Details | X Series | | X Series | X Series | X Series |
| | Model Number | | RSAS12CBEA | RSAS18CBEA | RMA524CBEA |
| | Tonnage | TR. | 1 | 1.5 | 2 |
| | Compressor | Type / Refrigerant | Tropical Rotary / R410a | Tropical Rotary / R410a | Tropical Twin Rotary / R410a |
| Performance | Rated Cooling Capacity (100 % load) | BTU / Hr (Watts) | 12000 (3520) | 18000 (5275) | 24000 (7034) |
| | Maximum Cooling Capacity | BTU / Hr (Watts) | 13210 (3870) | 20600 (6040) | 26100 (7650) |
| | Rated ISEER | | 5.75 | 5 | 4.7 |
| | Annual Power Consumption (As per BEE norms) | (kWh) | 473.69 | 816.15 | 1158.94 |
| | Fan Speed | No. of steps | 5 | 5 | 5 |
| | Air Flow (IDU) (Cooling-Super High) | CFM | 460 | 583 | 620 |
| | Sound Level* | db | 27 | 31 | 37 |
| Electrical | Rated Power Supply | Volts / Hz / Phase | 230 / 50 / 1 | 230 / 50 / 1 | 230 / 50 / 1 |
| | Rated Power Input | Watts | 800 | 1420 | 2070 |
| | Rated Current Drawn | Amps | 3.66 | 6.5 | 9.5 |
| Hitachi air | Wave Blade Design | | ✓ | ✓ | ✓ |
| | Big Flow Deflector | | ✓ | ✓ | ✓ |
| | Auto Coil Dry Technology | | ✓ | ✓ | ✓ |
| | iFresh (FrostWash Technology) | | | | |
| | iClean+ (Auto Filter Cleaning Technology) | | ✓ | ✓ | ✓ |
| Advance Features | Expandable | | ✓ | ✓ | ✓ |
| | iSee (Image Sensor Technology) | | ✓ | ✓ | ✓ |
| | iSense (Activity Sensor Technology) | | ✓ | ✓ | ✓ |
| | 4 Way Air Swing | | ✓ | ✓ | ✓ |
| | Tropical Design | | ✓ | ✓ | ✓ |
| | 100% Cooling Capacity at 43°C | | ✓ | ✓ | ✓ |
| | 100% Inner Grooved Copper Tube | | ✓ | ✓ | ✓ |
| | SuperSlit Fins | | ✓ | ✓ | ✓ |
| | Stabiliser Free Operation | | ✓ | ✓ | ✓ |
| | Filter Clean Indicator | | | | |
| | High CFM | | | | |
| | Penta Sensor | | ✓ | ✓ | ✓ |
| | Stainless Steel Coated Filter | | ✓ | ✓ | ✓ |
| | SuperFine Mesh filter | | | | |
| On / Off Timer with Advance Start Up | | | | | |
| Key Features | On / Off Timer | | ✓ | ✓ | ✓ |
| | Hydrophilic Fins (Indoor Unit) | | ✓ | ✓ | ✓ |
| | Powerful Mode | | ✓ | ✓ | ✓ |
| | Auto Off | | ✓ | ✓ | ✓ |
| | One Touch Super Silent | | ✓ | ✓ | ✓ |
| | Heat Mode | | | | |
| | Smart Swing | | ✓ | ✓ | ✓ |
| | Asymmetric Swing | | ✓ | ✓ | ✓ |
| Assurance* | Backlight Remote Controller | | ✓ | ✓ | ✓ |
| | Compressor Warranty | 5 + 5 Years | ✓ | ✓ | ✓ |
| | Controller (PCB) Warranty | 1 + 4 Years | ✓ | ✓ | ✓ |
| | Extended Warranty on Entire Machine | 1 + 1 Years | ✓ | ✓ | ✓ |
| Dimensions | Compressor Warranty | 1 + 4 Years | | | |
| | Dimension (IDU) (W X H X D) | mm | 997 X 294 X 294 | 997 X 294 X 294 | 997 X 294 X 294 |
| | Dimension (ODU) (W X H X D) | mm | 750 X 548 X 288 | 750 X 548 X 288 | 792 X 600 X 299 |
| | Suction Line Diameter | mm (Inches) | 9.53 (3/8") | 12.7 (1/2") | 15.878 (5/8") |
| | Liquid Line Diameter | mm (Inches) | 6.35 (1/4") | 6.35 (1/4") | 6.35 (1/4") |
| Net Weight IDU / ODU | Kg | 14 / 31.5 | 14 / 33.8 | 14 / 47.6 | |

Notes:

Auto Mode, Cool Mode, Fan Mode, Dry Mode (better humidity control), LCD Remote Control, Auto Fan Speed, Auto Restart, Green Refrigerant, 43 Quality Test features are available in every model.

*At Super Silent fan speed & at a distance of 1 m.

Permissible maximum pipe length limit is up to 25 mtrs

Features may vary from model to model. Due to continuous research & development, specifications & features may change without prior notice.

*T&C apply. Offer available on select models only and subject to company's discretion. Offer can be withdrawn anytime without prior notice.

SPECIFICATIONS SPLIT AC - INVERTER MODELS

| | DESCRIPTION | UNIT | KASHIKOI 5300X | | |
|--------------------------------------|---|--------------------|-------------------------|-------------------------|------------------------------|
| | | | 5 | 5 | 5 |
| | Star Rating | | 5 | 5 | 5 |
| Details | X Series | | X Series | X Series | X Series |
| | Model Number | | RSOG512IDEA | RSOG518ICEA | RMOG524ICEA |
| | Tonnage | TR. | 1 | 1.5 | 2 |
| | Compressor | Type / Refrigerant | Tropical Rotary / R410a | Tropical Rotary / R410a | Tropical Twin Rotary / R410a |
| Performance | Rated Cooling Capacity (100 % load) | BTU / Hr (Watts) | 12000 (3520) | 18000 (5275) | 24000 (7034) |
| | Maximum Cooling Capacity | BTU / Hr (Watts) | 13210 (3870) | 20600 (6040) | 26100 (7650) |
| | Rated ISEER | | 5.1 | 4.7 | 4.7 |
| | Annual Power Consumption (As per BEE norms) | (kWh) | 533.88 | 869.21 | 1158.94 |
| | Fan Speed | No. of steps | 5 | 5 | 5 |
| | Air Flow (IDU) (Cooling-Super High) | CFM | 460 | 583 | 620 |
| | Sound Level* | db | 28 | 31 | 37 |
| Electrical | Rated Power Supply | Volts / Hz / Phase | 230 / 50 / 1 | 230 / 50 / 1 | 230 / 50 / 1 |
| | Rated Power Input | Watts | 835 | 1449 | 2070 |
| | Rated Current Drawn | Amps | 4.03 | 6.6 | 9.5 |
| Hitachi air | Wave Blade Design | | ✓ | ✓ | ✓ |
| | Big Flow Deflector | | ✓ | ✓ | ✓ |
| | Auto Coil Dry Technology | | ✓ | ✓ | ✓ |
| | iFresh (FrostWash Technology) | | | | |
| | iClean+ (Auto Filter Cleaning Technology) | | ✓ | ✓ | ✓ |
| Advance Features | Expandable | | ✓ | ✓ | ✓ |
| | iSee (Image Sensor Technology) | | | | |
| | iSense (Activity Sensor Technology) | | ✓ | ✓ | ✓ |
| | 4 Way Air Swing | | ✓ | ✓ | ✓ |
| | Tropical Design | | ✓ | ✓ | ✓ |
| | 100% Cooling Capacity at 43°C | | ✓ | ✓ | ✓ |
| | 100% Inner Grooved Copper Tube | | ✓ | ✓ | ✓ |
| | SuperSlit Fins | | ✓ | ✓ | ✓ |
| | Stabiliser Free Operation | | ✓ | ✓ | ✓ |
| | Filter Clean Indicator | | | | |
| | High CFM | | | | |
| | Penta Sensor | | ✓ | ✓ | ✓ |
| | Stainless Steel Coated Filter | | ✓ | ✓ | ✓ |
| | SuperFine Mesh filter | | | | |
| On / Off Timer with Advance Start Up | | | | | |
| Key Features | On / Off Timer | | ✓ | ✓ | ✓ |
| | Hydrophilic Fins (Indoor Unit) | | ✓ | ✓ | ✓ |
| | Powerful Mode | | ✓ | ✓ | ✓ |
| | Auto Off | | ✓ | ✓ | ✓ |
| | One Touch Super Silent | | ✓ | ✓ | ✓ |
| | Heat Mode | | | | |
| | Smart Swing | | | | |
| | Asymmetric Swing | | ✓ | ✓ | ✓ |
| Backlight Remote Controller | | ✓ | ✓ | ✓ | |
| Assurance* | Compressor Warranty | 5 + 5 Years | ✓ | ✓ | ✓ |
| | Controller (PCB) Warranty | 1 + 4 Years | ✓ | ✓ | ✓ |
| | Extended Warranty on Entire Machine | 1 + 1 Years | ✓ | ✓ | ✓ |
| | Compressor Warranty | 1 + 4 Years | | | |
| Dimensions | Dimension (IDU) (W X H X D) | mm | 997 X 294 X 258 | 997 X 294 X 258 | 997 X 294 X 258 |
| | Dimension (ODU) (W X H X D) | mm | 750 X 548 X 288 | 750 X 548 X 288 | 792 X 600 X 299 |
| | Suction Line Diameter | mm (Inches) | 9.53 (3/8") | 12.7 (1/2") | 15.878 (5/8") |
| | Liquid Line Diameter | mm (Inches) | 6.35 (1/4") | 6.35 (1/4") | 6.35 (1/4") |
| | Net Weight IDU / ODU | Kg | 13 / 28 | 13 / 32.0 | 13 / 47.6 |

Notes:

Auto Mode, Cool Mode, Fan Mode, Dry Mode (better humidity control), LCD Remote Control, Auto Fan Speed, Auto Restart, Green Refrigerant, 43 Quality Test features are available in every model.

*At Super Silent fan speed & at a distance of 1 m.

Permissible maximum pipe length limit is up to 25 mtrs

Features may vary from model to model. Due to continuous research & development, specifications & features may change without prior notice.

*T&C apply. Offer available on select models only and subject to company's discretion. Offer can be withdrawn anytime without prior notice.

SPECIFICATIONS SPLIT AC - INVERTER MODELS

| | DESCRIPTION | UNIT | KASHIKOI 5200FX | | |
|--------------------------------------|---|--------------------|-------------------------|-------------------------|-----------------------------|
| | | | 5 | 5 | 5 |
| | Star Rating | | 5 | 5 | 5 |
| Details | X Series | | X Series | X Series | X Series |
| | Model Number | | RSFG512FDEA | RSOG518FDEA | RMOG524FDEA |
| | Tonnage | TR. | 1 | 1.5 | 2 |
| | Compressor | Type / Refrigerant | Tropical Rotary / R410a | Tropical Rotary / R410a | Tropical Twin Rotary / 410a |
| Performance | Rated Cooling Capacity (100 % load) | BTU / Hr (Watts) | 12000 (3516) | 18000 (5275) | 24000 (7034) |
| | Maximum Cooling Capacity | BTU / Hr (Watts) | 13200 (3870) | 19000 (5568) | 26100 (7650) |
| | Rated ISEER | | 4.6 | 4.55 | 4.7 |
| | Annual Power Consumption (As per BEE norms) | (kWh) | 592.12 | 897.84 | 1158.94 |
| | Fan Speed | No. of steps | 5 | 5 | 5 |
| | Air Flow (IDU) (Cooling-Super High) | CFM | 425 | 620 | 620 |
| | Sound Level* | db | 30 | 34 | 37 |
| Electrical | Rated Power Supply | Volts / Hz / Phase | 230 / 50 / 1 | 230 / 50 / 1 | 230 / 50 / 1 |
| | Rated Power Input | Watts | 924 | 1540 | 2070 |
| | Rated Current Drawn | Amps | 4.23 | 7.05 | 9.5 |
| Hitachi air | Wave Blade Design | | ✓ | ✓ | ✓ |
| | Big Flow Deflector | | ✓ | ✓ | ✓ |
| | Auto Coil Dry Technology | | ✓ | ✓ | ✓ |
| | iFresh (FrostWash Technology) | | ✓ | ✓ | ✓ |
| | iClean+ (Auto Filter Cleaning Technology) | | | | |
| Advance Features | Expandable | | ✓ | ✓ | ✓ |
| | iSee (Image Sensor Technology) | | | | |
| | iSense (Activity Sensor Technology) | | | | |
| | 4 Way Air Swing | | | | |
| | Tropical Design | | ✓ | ✓ | ✓ |
| | 100% Cooling Capacity at 43°C | | ✓ | ✓ | ✓ |
| | 100% Inner Grooved Copper Tube | | ✓ | ✓ | ✓ |
| | SuperSlit Fins | | ✓ | ✓ | ✓ |
| | Stabiliser Free Operation | | ✓ | ✓ | ✓ |
| | Filter Clean Indicator | | | | |
| | High CFM | | | | |
| | Penta Sensor | | ✓ | ✓ | ✓ |
| | Stainless Steel Coated Filter | | | | |
| | SuperFine Mesh filter | | ✓ | ✓ | ✓ |
| On / Off Timer with Advance Start Up | | | | | |
| Key Features | On / Off Timer | | ✓ | ✓ | ✓ |
| | Hydrophilic Fins (Indoor Unit) | | ✓ | ✓ | ✓ |
| | Powerful Mode | | | | |
| | Auto Off | | | | |
| | One Touch Super Silent | | ✓ | ✓ | ✓ |
| | Heat Mode | | | | |
| | Smart Swing | | | | |
| | Asymmetric Swing | | | | |
| Assurance* | Backlight Remote Controller | | ✓ | ✓ | ✓ |
| | Compressor Warranty | 5 + 5 Years | ✓ | ✓ | ✓ |
| | Controller (PCB) Warranty | 1 + 4 Years | ✓ | ✓ | ✓ |
| | Extended Warranty on Entire Machine | 1 + 1 Years | ✓ | ✓ | ✓ |
| Dimensions | Compressor Warranty | 1 + 4 Years | | | |
| | Dimension (IDU) (W X H X D) | mm | 798 X 295 X 239 | 997 X 294 X 253 | 997 X 294 X 253 |
| | Dimension (ODU) (W X H X D) | mm | 750 X 548 X 288 | 750 X 548 X 288 | 792 X 600 X 299 |
| | Suction Line Diameter | mm (Inches) | 9.53 (3/8") | 12.7 (1/2") | 15.878 (5/8") |
| | Liquid Line Diameter | mm (Inches) | 6.35 (1/4") | 6.35 (1/4") | 6.35 (1/4") |
| Net Weight IDU / ODU | Kg | 9.5 / 27.9 | 13 / 32.4 | 13 / 47.6 | |

Notes: Auto Mode, Cool Mode, Fan Mode, Dry Mode (better humidity control), LCD Remote Control, Auto Fan Speed, Auto Restart, Green Refrigerant, 43 Quality Test features are available in every model.

*At Super Silent fan speed & at a distance of 1 m.

Permissible maximum pipe length limit is up to 25 mtrs

Features may vary from model to model. Due to continuous research & development, specifications & features may change without prior notice.

*T&C apply. Offer available on select models only and subject to company's discretion. Offer can be withdrawn anytime without prior notice.

SPECIFICATIONS SPLIT AC - INVERTER MODELS

| | DESCRIPTION | UNIT | KASHIKOI 5100X++ |
|--------------------------------------|---|--------------------|-------------------------|
| | Star Rating | | 5 |
| Details | X Series | | X Series |
| | Model Number | | RSOG512HCEAP |
| | Tonnage | TR. | 1 |
| | Compressor | Type / Refrigerant | Tropical Rotary / R410a |
| Performance | Rated Cooling Capacity (100 % load) | BTU / Hr (Watts) | 12215 (3580) |
| | Maximum Cooling Capacity | BTU / Hr (Watts) | 15015 (4400) |
| | Rated ISEER | | 6.1 |
| | Annual Power Consumption (As per BEE norms) | (kWh) | 454.6 |
| | Fan Speed | No. of steps | 5 |
| | Air Flow (IDU) (Cooling-Super High) | CFM | 484 |
| | Sound Level* | db | 27 |
| Electrical | Rated Power Supply | Volts / Hz / Phase | 230 / 50 / 1 |
| | Rated Power Input | Watts | 741 |
| | Rated Current Drawn | Amps | 3.58 |
| Hitachi air | Wave Blade Design | | ✓ |
| | Big Flow Deflector | | ✓ |
| | Auto Coil Dry Technology | | ✓ |
| | iFresh (FrostWash Technology) | | |
| | iClean+ (Auto Filter Cleaning Technology) | | |
| Advance Features | Expandable | | ✓ |
| | iSee (Image Sensor Technology) | | |
| | iSense (Activity Sensor Technology) | | |
| | 4 Way Air Swing | | |
| | Tropical Design | | ✓ |
| | 100% Cooling Capacity at 43°C | | ✓ |
| | 100% Inner Grooved Copper Tube | | ✓ |
| | SuperSlit Fins | | ✓ |
| | Stabiliser Free Operation | | ✓ |
| | Filter Clean Indicator | | ✓ |
| | High CFM | | |
| | Penta Sensor | | ✓ |
| | Stainless Steel Coated Filter | | |
| | SuperFine Mesh filter | | ✓ |
| On / Off Timer with Advance Start Up | | | |
| Key Features | On / Off Timer | | ✓ |
| | Hydrophilic Fins (Indoor Unit) | | ✓ |
| | Powerful Mode | | |
| | Auto Off | | |
| | One Touch Super Silent | | ✓ |
| | Heat Mode | | |
| | Smart Swing | | |
| | Asymmetric Swing | | |
| Backlight Remote Controller | | ✓ | |
| Assurance* | Compressor Warranty | 5 + 5 Years | ✓ |
| | Controller (PCB) Warranty | 1 + 4 Years | ✓ |
| | Extended Warranty on Entire Machine | 1 + 1 Years | ✓ |
| | Compressor Warranty | 1 + 4 Years | |
| Dimensions | Dimension (IDU) (W X H X D) | mm | 997 X 294 X 253 |
| | Dimension (ODU) (W X H X D) | mm | 750 X 548 X 288 |
| | Suction Line Diameter | mm (Inches) | 9.53 (3/8") |
| | Liquid Line Diameter | mm (Inches) | 6.35 (1/4") |
| | Net Weight IDU / ODU | Kg | 13 / 33.3 |

Notes:

Auto Mode, Cool Mode, Fan Mode, Dry Mode (better humidity control), LCD Remote Control, Auto Fan Speed, Auto Restart, Green Refrigerant, 43 Quality Test features are available in every model.

*At Super Silent fan speed & at a distance of 1 m.

Permissible maximum pipe length limit is up to 25 mtrs

Features may vary from model to model. Due to continuous research & development, specifications & features may change without prior notice.

*T&C apply. Offer available on select models only and subject to company's discretion. Offer can be withdrawn anytime without prior notice.

SPECIFICATIONS SPLIT AC - INVERTER MODELS

| | DESCRIPTION | UNIT | KASHIKOI 5100X+ | |
|--------------------------------------|---|--------------------|-------------------------|-------------------------|
| | Star Rating | | 5 | 5 |
| Details | X Series | | X Series | X Series |
| | Model Number | | RSNG512HCEAP | RSOG518HCEAP |
| | Tonnage | TR. | 1 | 1.5 |
| | Compressor | Type / Refrigerant | Tropical Rotary / R410a | Tropical Rotary / R410a |
| Performance | Rated Cooling Capacity (100 % load) | BTU / Hr (Watts) | 12000 (3520) | 18000 (5275) |
| | Maximum Cooling Capacity | BTU / Hr (Watts) | 13200 (3870) | 20600 (6040) |
| | Rated ISEER | | 5.24 | 5.2 |
| | Annual Power Consumption (As per BEE norms) | (kWh) | 520.21 | 785.36 |
| | Fan Speed | No. of steps | 5 | 5 |
| | Air Flow (IDU) (Cooling-Super High) | CFM | 460 | 583 |
| | Sound Level* | db | 28 | 31 |
| Electrical | Rated Power Supply | Volts / Hz / Phase | 230 / 50 / 1 | 230 / 50 / 1 |
| | Rated Power Input | Watts | 812 | 1368 |
| | Rated Current Drawn | Amps | 3.92 | 6.26 |
| Hitachi air | Wave Blade Design | | ✓ | ✓ |
| | Big Flow Deflector | | ✓ | ✓ |
| | Auto Coil Dry Technology | | ✓ | ✓ |
| | iFresh (FrostWash Technology) | | | |
| | iClean+ (Auto Filter Cleaning Technology) | | | |
| Advance Features | Expandable | | ✓ | ✓ |
| | iSee (Image Sensor Technology) | | | |
| | iSense (Activity Sensor Technology) | | | |
| | 4 Way Air Swing | | | |
| | Tropical Design | | ✓ | ✓ |
| | 100% Cooling Capacity at 43°C | | ✓ | ✓ |
| | 100% Inner Grooved Copper Tube | | ✓ | ✓ |
| | SuperSlit Fins | | ✓ | ✓ |
| | Stabiliser Free Operation | | ✓ | ✓ |
| | Filter Clean Indicator | | ✓ | ✓ |
| | High CFM | | | |
| | Penta Sensor | | ✓ | ✓ |
| | Stainless Steel Coated Filter | | | |
| | SuperFine Mesh filter | | ✓ | ✓ |
| On / Off Timer with Advance Start Up | | | | |
| Key Features | On / Off Timer | | ✓ | ✓ |
| | Hydrophilic Fins (Indoor Unit) | | ✓ | ✓ |
| | Powerful Mode | | | |
| | Auto Off | | | |
| | One Touch Super Silent | | ✓ | ✓ |
| | Heat Mode | | | |
| | Smart Swing | | | |
| | Asymmetric Swing | | | |
| Backlight Remote Controller | | ✓ | ✓ | |
| Assurance* | Compressor Warranty | 5 + 5 Years | ✓ | ✓ |
| | Controller (PCB) Warranty | 1 + 4 Years | ✓ | ✓ |
| | Extended Warranty on Entire Machine | 1 + 1 Years | ✓ | ✓ |
| | Compressor Warranty | 1 + 4 Years | | |
| Dimensions | Dimension (IDU) (W X H X D) | mm | 968 X 294 X 240 | 997 X 294 X 253 |
| | Dimension (ODU) (W X H X D) | mm | 750 X 548 X 288 | 750 X 548 X 288 |
| | Suction Line Diameter | mm (Inches) | 9.53 (3/8") | 12.7 (1/2") |
| | Liquid Line Diameter | mm (Inches) | 6.35 (1/4") | 6.35 (1/4") |
| | Net Weight IDU / ODU | Kg | 11.2 / 31 | 13 / 33.8 |

Notes:
Auto Mode, Cool Mode, Fan Mode, Dry Mode (better humidity control), LCD Remote Control, Auto Fan Speed, Auto Restart, Green Refrigerant, 43 Quality Test features are available in every model.

*At Super Silent fan speed & at a distance of 1 m.

Permissible maximum pipe length limit is up to 25 mtrs

Features may vary from model to model. Due to continuous research & development, specifications & features may change without prior notice.

*T&C apply. Offer available on select models only and subject to company's discretion. Offer can be withdrawn anytime without prior notice.

SPECIFICATIONS SPLIT AC - INVERTER MODELS

| DESCRIPTION | UNIT | KASHIKOI 5100X | | | |
|---|--------------------|-------------------------|-------------------------|-------------------------|------------------------------|
| | | 5 | 5 | 5 | 5 |
| Star Rating | | 5 | 5 | 5 | 5 |
| X Series | | X Series | X Series | X Series | X Series |
| Model Number | | RSFG512HDEA | RSNG515HDEA | RSOG518HDEA | RMOG524HCEA |
| Tonnage | TR. | 1 | 1.25 | 1.5 | 2 |
| Compressor | Type / Refrigerant | Tropical Rotary / R410a | Tropical Rotary / R410a | Tropical Rotary / R410a | Tropical Twin Rotary / R410a |
| Rated Cooling Capacity (100% load) | BTU / Hr (Watts) | 12000 (3516) | 15000 (4400) | 18000 (5275) | 24000 (7034) |
| Maximum Cooling Capacity | BTU / Hr (Watts) | 13200 (3870) | 15800 (4630) | 19000 (5568) | 26100 (7650) |
| Rated ISEER | | 4.6 | 4.65 | 4.55 | 4.7 |
| Annual Power Consumption (As per BEE norms) | (kWh) | 592.12 | 732.69 | 897.84 | 1158.94 |
| Fan Speed | No. of steps | 5 | 5 | 5 | 5 |
| Air Flow (IDU) (Cooling-Super High) | CFM | 425 | 530 | 620 | 620 |
| Sound Level* | db | 30 | 30 | 34 | 37 |
| Rated Power Supply | Volts / Hz / Phase | 230 / 50 / 1 | 230 / 50 / 1 | 230 / 50 / 1 | 230 / 50 / 1 |
| Rated Power Input | Watts | 924 | 1249 | 1540 | 2070 |
| Rated Current Drawn | Amps | 4.23 | 5.72 | 7.05 | 9.5 |
| Wave Blade Design | | ✓ | ✓ | ✓ | ✓ |
| Big Flow Deflector | | ✓ | ✓ | ✓ | ✓ |
| Auto Coil Dry Technology | | ✓ | ✓ | ✓ | ✓ |
| iFresh (FrostWash Technology) | | | | | |
| iClean+ (Auto Filter Cleaning Technology) | | | | | |
| Expandable | | ✓ | ✓ | ✓ | ✓ |
| iSee (Image Sensor Technology) | | | | | |
| iSense (Activity Sensor Technology) | | | | | |
| 4 Way Air Swing | | | | | |
| Tropical Design | | ✓ | ✓ | ✓ | ✓ |
| 100% Cooling Capacity at 43°C | | ✓ | ✓ | ✓ | ✓ |
| 100% Inner Grooved Copper Tube | | ✓ | ✓ | ✓ | ✓ |
| SuperSlit Fins | | ✓ | ✓ | ✓ | ✓ |
| Stabiliser Free Operation | | ✓ | ✓ | ✓ | ✓ |
| Filter Clean Indicator | | ✓ | ✓ | ✓ | ✓ |
| High CFM | | | | | |
| Penta Sensor | | ✓ | ✓ | ✓ | ✓ |
| Stainless Steel Coated Filter | | | | | |
| SuperFine Mesh filter | | ✓ | ✓ | ✓ | ✓ |
| On / Off Timer with Advance Start Up | | | | | |
| On / Off Timer | | ✓ | ✓ | ✓ | ✓ |
| Hydrophilic Fins (Indoor Unit) | | ✓ | ✓ | ✓ | ✓ |
| Powerful Mode | | | | | |
| Auto Off | | | | | |
| One Touch Super Silent | | ✓ | ✓ | ✓ | ✓ |
| Heat Mode | | | | | |
| Smart Swing | | | | | |
| Asymmetric Swing | | | | | |
| Backlight Remote Controller | | ✓ | ✓ | ✓ | ✓ |
| Compressor Warranty | 5 + 5 Years | ✓ | ✓ | ✓ | ✓ |
| Controller (PCB) Warranty | 1 + 4 Years | ✓ | ✓ | ✓ | ✓ |
| Extended Warranty on Entire Machine | 1 + 1 Years | ✓ | ✓ | ✓ | ✓ |
| Compressor Warranty | 1 + 4 Years | | | | |
| Dimension (IDU) (W X H X D) | mm | 798 X 295 X 239 | 968 X 294 X 240 | 997 X 294 X 253 | 997 X 294 X 253 |
| Dimension (ODU) (W X H X D) | mm | 750 X 548 X 288 | 750 X 548 X 288 | 750 X 548 X 288 | 792 X 600 X 299 |
| Suction Line Diameter | mm (Inches) | 9.53 (3/8") | 9.53 (3/8") | 12.7 (1/2") | 15.878 (5/8") |
| Liquid Line Diameter | mm (Inches) | 6.35 (1/4") | 6.35 (1/4") | 6.35 (1/4") | 6.35 (1/4") |
| Net Weight IDU / ODU | Kg | 9.5 / 27.9 | 11.2 / 28.70 | 13 / 32.4 | 13 / 47.6 |

Notes:

Auto Mode, Cool Mode, Fan Mode, Dry Mode (better humidity control), LCD Remote Control, Auto Fan Speed, Auto Restart, Green Refrigerant, 43 Quality Test features are available in every model.

*At Super Silent fan speed & at a distance of 1 m.

Permissible maximum pipe length limit is up to 25 mtrs

Features may vary from model to model. Due to continuous research & development, specifications & features may change without prior notice.

*T&C apply. Offer available on select models only and subject to company's discretion. Offer can be withdrawn anytime without prior notice.